


HONEY CEILING LIGHT

Code: HO-OPLZ01L108

These particular LED panels are the modern evolution of ceiling and wall lights: a versatile product at the service of the most demanding requirements, which embraces every space and every dimension. This type of solution is very common in large spaces and is also used in work environments where the quality of light is a fundamental factor.



General specifications

Designer	Elcom Design Team
Commercial brand	Honey
Installation environment	Interior
Native mounting type	Surface mounted
Mounting type	Surface mountend
Ideal application locations	Uffici
Cable output type	Rear IN
Customizable	Yes
Made in	Italy

Physical specifications

Shape	Rectangular
Body material	Aluminum
Body finish	Matte
Body color	White
Covering with insulating materials	No
IP	IP20

Lighting specifications

N° of light sources	1
Lumen	3600
Source lumen	7200

Power	60
Light type	White
CCT	2700K
CRI	93
R9	50
SDCM	3
UGR	< 24
RG	RG0
Life time	L80B50
LB value @ h	50000

Optical specifications

Emission type	Direct monoemission
Light emission side	Bottom
Light beam distribution	Symmetric
Beam	120
Optics type	Flat diffuser
Optical diffuser finish	Opal
Optical diffuser material	PMMA
Internal diffuser type	Plexiglass diffuser

Electrical specifications

Power supply availability	Not included
Power supply position	Remote
Ignition type	Single switch
Dimmable	Yes
Dimmer availability	Not included
Dimming type	ON/OFF
Dimmer position	Remote
Power supply voltage type	DC
Power supply type	Voltage
Input Voltage (V)	24
Insulation class	III
Cable 1 pole number	2
Light source type	LEDs SMD
Energy efficiency class	E
Replaceable light source	Replaceable by skilled personnel

Dimensions and weight

Length (mm)	1008
Width (mm)	873
Height / Thickness (mm)	19
Recess length (mm)	1008
Recess width (mm)	873
Cable 1 length (mm)	2000

General conditions

Warranty	2 years
----------	---------