

## KIEV 40W 4000K 3100LM 40° 220V D188MM

**Code: KI40-N**

The downlights spread general or accent light, keeping high luminous efficiency. The low luminance is combined with extremely low glare levels, thanks to the recessed optics and a wide range of accessories. You can choose among many versions: with round or square bezel, with a fixed or tiltable optic, trimless or with low recessed height. In the swivel version, they allow an additional level of versatility that adapts to any environment and allows you to create targeted lighting.



### General specifications

|                             |  |
|-----------------------------|--|
| Designer                    | Elcom Design Team  |
| Installation environment    | Interior   |
| Native mounting type        | Rebated flush-mounted  |
| Mounting type               | Rebated flush-mounted  |
| Ideal application locations | Residential, Hospitality, Showroom, Museum, Office, Commercial space |
| Packaging                   | Box  |
| Made in                     | Italy  |

### Physical specifications

|                                    |          |
|------------------------------------|----------|
| Shape                              | Round    |
| Body material                      | Aluminum |
| Body finish                        | Matte    |
| Body color                         | White    |
| Frontal material                   | Aluminum |
| Frontal finish                     | Matte    |
| Frontal color                      | White    |
| Thermal dissipation                | Passive  |
| Covering with insulating materials | No       |
| IP                                 | IP20     |
| Waterstop                          | No       |

|                      |    |
|----------------------|----|
| Salt mist resistance | No |
|----------------------|----|

## Lighting specifications

|            |        |
|------------|--------|
| Lumen      | 3100   |
| Power      | 40     |
| W source   | 40     |
| Light type | White  |
| CCT        | 4000K  |
| CRI        | 90     |
| Life time  | L70B50 |

## Optical specifications

|                         |                          |
|-------------------------|--------------------------|
| Light beam distribution | Symmetric                |
| Beam                    | 40                       |
| Optics type             | Symmetrical optical lens |
| Optical diffuser finish | Transparent              |
| Orientability           | Oscillating              |

## Electrical specifications

|                           |          |
|---------------------------|----------|
| Power supply availability | Included |
| Power supply position     | Remote   |
| Dimmable                  | No       |
| Dimming type              | ON/OFF   |
| Power supply type         | Current  |
| Input Voltage (V)         | 230      |

## Dimensions and weight

|                          |     |
|--------------------------|-----|
| Height / Thickness (mm)  | 159 |
| Diameter (mm)            | 188 |
| Recessed hole width (mm) | 172 |